

Instructions (2)

Electronic alarm-system, wireless,
for children who wet their bed (nocturnal enuresis)



▶ AFTER THE NOCTURNAL MICTION



Remove and throw the paper in the bin
(change the paper every day to avoid
false alarms)



Separate the transmitter and the urine-detector. This stops the alarm!
If the alarm was longer than 3 minutes, press briefly one of the two
loudness push-buttons on the receiver to stop the alarm



Clean the urine-detector and the transmitter under tepid
running water



Wipe the urine-detector and transmitter dry.
Do not rub the urine-detector!

Report the result of the night on the diagram / Do not reinstall the Pipi-Stop for the rest of the night.

▶ TEST OF THE SYSTEM **A test with water does not give an alarm!**



Test of the receiver



Insert the round
plug of the
power supply at
the rear of the
receiver

Plug power supply into an electrical outlet 230V
Press briefly on one of the 2 loudness
push-buttons

✓ **blue light is lit + sound**

Test of the transmitter



Shunt out the 2 snap fasteners of the
transmitter with a metallic coffee spoon

✓ **Sound + white flashing light**

Test of the whole system



Transmitter
at the rear

Fix the transmitter on the detector and
shunt out the tongue with a coffee spoon
(urine-detector must be unpacked)

✓ **Sound + white flashing light**

If there is no alarm: check that the receiver and the transmitter are not too far away from each other.

▶ ADJUSTMENT OF THE LOUDNESS (if necessary) **Please do not press both push-buttons simultaneously!**

Reduce volume:

press the left button (↓)
and hold until you reach the
desired loudness



Increase volume:

press the right button
(↑) and hold until you reach
the desired loudness

The loudness is
automatically
stored (even
when a power
failure occurs).

If the Pipi-Stop system does not work after these checks, please contact us immediately.

▶ SECURITY / MAINTENANCE



Warning!

- Receiver and power supply should **never** be in contact with water (danger of electrical shock!)
- The transmitter should **never** be opened. The battery can only be changed by Melebi SA (guarantee of water tightness!)
- Use **only our 12V power supply with our receiver to avoid overvoltage!**
- All the repairing is **exclusively** done by Melebi SA.

Please return us by mail in the original box after the treatment:

- The **completed diagram**
- **All the rented parts** (refer to the picture in the cover of the box)